

Straight Fuel Line Quick Connectors 7.89 x 8mm 3pc

A set of 3 different sized straight fuel line quick connectors allowing for tight connections on 8mm fuel lines. Quick connectors are designed for the automotive industry for the transfer of fuel, oil, water cooling systems and air. The self locking connector enables it to be connected & disconnected with ease and speed, with the wide operating temperature range ensures it can cope with the extreme temperatures that could lead to cracking and leaks. To ease the fitting of the hard plastic fuel pipe to the connectors, use Laser Tools Pipe Connector Insertion Tool, Part No. 6933.



Additional Information

- Straight connectors, suits: 8mm ID nylon pipe; 7.5mm ID rubber hose.
- Constant running pressure: 5 bar (72psi); max pressure: 7 bar (101psi). Operating temperature: -40°C to 120°C.
- Body manufactured from nylon PA12; O-ring from FKM seal (viton). Made to SAE J2044-2009 standards.
- Grey tab for fuel identification (note: AdBlue® specific connectors have red tabs).
- Included in assorted boxes of straight quick fuel line connectors, Part No. 34031 & mixed set of straight & angled connectors, Part No. 34029. Also available in assorted fuel & pipe connector kits, Part Nos. 37011 & 37199.


<http://product/37213>



Related Tools



Button Connector Pliers with Flexible Cable | 7407



Hose Clamp Plier Set - Interchangeable | 7408



Pipe Connector Insertion Tool | 6933



Pneumatic Diesel Bleeding Kit | 7174



Diesel Fuel Line Blank Set 12pc | 7098



Scarab Quick Connector Disconnect Tool | 7826